

AM - 106 / ATD - 106

AM-106: non-wire, flat component printing

ATD-106: off-line wire and sleeve printing



AM-106



ATD-106

AM - 106

- Prints on plastics, electronic connectors, and many industrial components
- Utilizes individual steel type or custom dies and logos for unlimited special applications
- Prints one-, two- or three-line legends on a wide range of surfaces
- Prints horizontally or vertically
- The ideal solution for nylon Panduit or Thomas and Betts style cable printers
- Lightweight, portable and inexpensive to operate
- Oversized 4" x 6" base plate easily accommodates odd-shaped plastic connectors, parts and assemblies
- Print area: sizes up to 1" x 3"
- Hand operated model available

ATD - 106

- For insulated wire and cable, heat-shrink sleeving, rigid or thin-wall flexible tubing and multi-lumen medical tubing
- Utilizes individual steel type
- Prints one-, two- or three-line legends on sleeving
- Prints horizontally or vertically
- Interchangeable fixture design prints various substrates with precision
- Lightweight, portable and inexpensive to operate
- Prints on wire on sizes from .035" to .750" OD
- Prints on sleeving on sizes from .093" to 2.0" ID
- Hand operated model available

Kingsley

A DIVISION OF ITW

Kingsley

A DIVISION OF ITW

2538 Wisconsin Avenue
Downers Grove, IL 60515-4293
Phone: 630.968.0647 Fax: 630.968.7672
800.421.0995
info@itwnorwood.com www.itwnorwood.com

AM - 106

ATD - 106

Application	Plastic parts, cable ties, tags, ID markers, tapes, labels, heat-shrink sleeving up to 3" ID	Wire—sizes .035" to .750" OD Sleeving—sizes .093" to 2.0" ID				
Operation	Pneumatic, foot pedal activated					
Printing Method	Hot stamp process; individually set alpha-numeric type and/or unitized engraved					
Printing Characteristics	One-, two- or three line, horizontal or vertical printing	Wire: One-line, horizontal or vertical printing along the wire or simultaneous end printing with appropriate wire holding fixtures. Sleeving: one- two- or three-line, horizontal or vertical printing.				
Printing Area	<table border="0"> <tr> <td>English 1"x 3"</td> <td>Metric 25 mm x 101 mm</td> </tr> </table>	English 1"x 3"	Metric 25 mm x 101 mm	<table border="0"> <tr> <td>English Wire: 1 line x 2" or 1 line x 2.9" on sizes .035" to .750" (with WFT fixture) OD- Sleeving: 1,2, or 3 lines x 2.9" on sizes .093" to 2.0" ID</td> <td>Metric Wire: 1 line x 50.8 mm or 1 line x 73.6 mm on sizes .889 to 19 mm (with WFT fixture) OD Sleeving: 1,2, or 3 lines x 73 mm on sizes 2.3 mm to 50.8 mm ID</td> </tr> </table>	English Wire: 1 line x 2" or 1 line x 2.9" on sizes .035" to .750" (with WFT fixture) OD- Sleeving: 1,2, or 3 lines x 2.9" on sizes .093" to 2.0" ID	Metric Wire: 1 line x 50.8 mm or 1 line x 73.6 mm on sizes .889 to 19 mm (with WFT fixture) OD Sleeving: 1,2, or 3 lines x 73 mm on sizes 2.3 mm to 50.8 mm ID
English 1"x 3"	Metric 25 mm x 101 mm					
English Wire: 1 line x 2" or 1 line x 2.9" on sizes .035" to .750" (with WFT fixture) OD- Sleeving: 1,2, or 3 lines x 2.9" on sizes .093" to 2.0" ID	Metric Wire: 1 line x 50.8 mm or 1 line x 73.6 mm on sizes .889 to 19 mm (with WFT fixture) OD Sleeving: 1,2, or 3 lines x 73 mm on sizes 2.3 mm to 50.8 mm ID					
Hot Stamp Foil	Kingsley bulk foil in 100' rolls. See Kingsley Foil Data Sheets for complete selection and specifications.					
Power Requirement	110V standard; 220V available	110V standard; 220V available				
Air Requirement	100 PSI / 5 CFM	100 PSI / 5 CFM				
Controls	On/off switch with power on indicator; adjustable temperature controller with indicator; solid-state dwell timer; air pressure regulator and moisture trap					
Machine Supplied With	Large 4"x 6" base plate; cycle counter; heavy duty grounded power cord	Heavy duty grounded power cord; safety guard; single-line adapter sleeve				
Required Accessories	Kingsley type and spacers; one-, two- or three-line type holders; Kingsley foil	Kingsley type and spacers; wire-holding/sleeve-holding fixtures by material size; one-, two- or three-line type holders; Kingsley foil				
Recommended Accessories	See Kingsley Data Sheets for complete selection and specifications.					
	Type box; spacer tray	Type box; spacer tray				
Dimensions	<table border="0"> <tr> <td>English Height: 16.0" Width: 10.5" Depth: 18.0"</td> <td>Metric Height: 40.6 cm Width: 26.6 cm Depth: 45.7 cm</td> </tr> </table>	English Height: 16.0" Width: 10.5" Depth: 18.0"	Metric Height: 40.6 cm Width: 26.6 cm Depth: 45.7 cm	<table border="0"> <tr> <td>English Height: 15.5" Width: 11.0" Depth: 18.0"</td> <td>Metric Height: 39.3 cm Width: 27.9 cm Depth: 45.7 cm</td> </tr> </table>	English Height: 15.5" Width: 11.0" Depth: 18.0"	Metric Height: 39.3 cm Width: 27.9 cm Depth: 45.7 cm
English Height: 16.0" Width: 10.5" Depth: 18.0"	Metric Height: 40.6 cm Width: 26.6 cm Depth: 45.7 cm					
English Height: 15.5" Width: 11.0" Depth: 18.0"	Metric Height: 39.3 cm Width: 27.9 cm Depth: 45.7 cm					
Weight	Net: 45 lbs.; Shipping: 50 lbs.	Net: 45 lbs.; Shipping: 50 lbs.				

Optional CE safety guarding available on domestic machines

Pricing and specifications are subject to change