



A DIVISION OF ITW

## ENGRAVED STEEL TYPEWHEELS

All Kingsley typewheels have forty characters (letters A-Z, Numbers 0-9 and special characters: left arrow, right arrow, hyphen, and blank). Typewheel machines mark one line of type. Typewheel selection for wire is insulation O.D. dependent, with the VW-026K wheel offering the broadest operating range. Curved face typewheels are available in vertical reading (top to bottom) and horizontal reading (left to right) formats.

## WIRE MARKING TYPEWHEELS

(for use with Models E302, SL-14, and Autowire-23 series machines, KIP-20, and Modprints)

### Curved Face, Vertical

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
VW-026K	0.068"	0.100"	.038"-.175"

### Curved Face, Horizontal

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
DW-28K	0.042"	0.100"	.050" - .075"
RW-38K	0.050"	0.100"	.068" - .096"
SW-55K	0.082"	0.100"	.096" - .166"
LW-125K	0.098"	0.100"	.166" - .350"

### Flat Face, Horizontal

Part Number	Character Radius	Wheel Width	O.D. of Wire Insulation*
FF-332K	3/32"	0.100"	0.310" - 0.400"
FF-125K	1/4"	0.100"	0.400" and > Custom

\*Wire insulation O.D. range specified is for PVC insulation. Harder insulation reduces this range.

**Please contact our Customer Service Department for current pricing.**

2538 Wisconsin Avenue  
Downers Grove, IL 60515 USA

[www.itwnorwood.com](http://www.itwnorwood.com)  
[info@itwnorwood.com](mailto:info@itwnorwood.com)

Phone: 800-626-3464, 630-968-0646  
Fax: 630-968-7672